

单相

- 自愈式低压并联电容器(单相)
- Self-healing Type Low Voltage Shunt Capacitor(Single-phase)



主要规格

产品型号	额定电压 (kV)	额定容量 (kvar)	额定电容 (μF)	额定电流 (A)	高度 H (mm)	出线端子	外壳类型
BSMJ、BCMJ、BZMJ							
0.23-1-1	0.23	1	60	4.3	130	M5	A1
0.23-3-1	0.23	3	181	13	130	M6	A
0.23-5-1	0.23	5	301	21.7	220	M6	A
0.23-8-1	0.23	8	481	34.8	220	M6	A
0.23-10-1	0.23	10	602	43.5	220	M8	B
0.23-12-1	0.23	12	722	52.2	220	M8	B
0.23-15-1	0.23	15	903	65.2	270	M8	B
0.23-18-1	0.23	18	1083	78.3	230	M10	C
0.23-20-1	0.23	20	1203	87	230	M10	C
0.23-25-1	0.23	25	1504	108.7	230	2×M10	C
0.23-30-1	0.23	30	1805	130.4	280	2×M10	C
0.4-1-1	0.4	1	20	2.5	105	M5	A1
0.4-3-1	0.4	3	60	7.5	130	M5	A1
0.4-5-1	0.4	5	100	12.5	130	M6	A
0.4-8-1	0.4	8	159	20	130	M6	A
0.4-10-1	0.4	10	199	25	185	M6	A
0.4-12-1	0.4	12	239	30	185	M6	A
0.4-15-1	0.4	15	299	37.5	220	M6	A
0.4-18-1B(A)	0.4	18	358	45	220(245)	M8(M8)	B(A)
0.4-20-1B(A)	0.4	20	398	50	220(245)	M8(M8)	B(A)

产品型号 BSMJ、BCMJ、BZMJ	额定电压 (kV)	额定容量 (kvar)	额定电容 (μ F)	额定电流 (A)	高度 H (mm)	出线端子	外壳类型
0.4-25-1	0.4	25	498	62.5	220	M8	B
0.4-30-1	0.4	30	597	75	270	M8	B
0.4-40-1	0.4	40	796	100	230	M10	C
0.4-50-1	0.4	50	994.7	125	230	2×M10	C
0.4-60-1	0.4	60	1193.7	150	280	2×M10	C
0.45-1-1	0.45	1	15.7	2.2	105	M5	A1
0.45-3-1	0.45	3	47	6.7	105	M5	A1
0.45-5-1	0.45	5	79	11	130	M6	A
0.45-8-1	0.45	8	126	18	130	M6	A
0.45-10-1	0.45	10	157	22	185	M6	A
0.45-12-1	0.45	12	189	27	185	M6	A
0.45-15-1	0.45	15	236	33.3	220	M8	A
0.45-18-1B(A)	0.45	18	283	40	220(245)	M8(M8)	B(A)
0.45-20-1B(A)	0.45	20	315	44.4	220(245)	M8(M8)	B(A)
0.45-25-1	0.45	25	393	55.6	220	M8	B
0.45-30-1	0.45	30	472	66.7	220	M8	B
0.45-40-1	0.45	40	629	88.9	230	M10	C
0.45-50-1	0.45	50	786	111	230	2×M10	C
0.45-60-1	0.45	60	943.1	133	230	2×M10	C

注：其它特殊规格型号产品根据用户要求供货。

安装及外形尺寸

